



AMERICAN SYN-TURF

BEST ARTIFICIAL GRASS

MADE IN THE USA



Cascade

USES

- ▶ General Landscape
- ▶ Lawns
- ▶ Pet Areas
- ▶ Roof Decks
- ▶ Medians
- ▶ Multi-Use Activity Areas
- ▶ Commercial or Residential



PFAS COMPLIANT



LEAD FREE

U-BLADE



SPECIFICATIONS

Pile Height: 1 3/4"

Turf Gauge: 1/2"

Face Weight: 70 oz./yd²

Backing Weight: 26 oz./yd²

Total Weight: 100 oz./yd²

Stitch Rate: 13/10cm

Stitches/M²: 13650

Material/Dtex: PE & PP 14400

Color: Field and Apple Green Face Fiber with Green and Tan Thatch

Type Of Fiber: PE Monofilament and PP Curled Thatch

Infill Amount: 1.0 lb./psf.

Primary Backing: Premium AST Backing

Tuft Bind: 13+ lb/force (ASTM D1335)

Blade Type: U-Blade

Permeability: 161.3 inches/hr. (ASTM F1551)

Melting Point: 176 °F (ASTM D2859)

Grab Tear MD: >200 lb./force (ASTM D5034)

Grab Tear CMD: >200 lb./force (ASTM D5034)

Roll Width: 15 If

Roll Length: 100 If

Sq. Ft. Per Roll: 1500

Total Roll Weight: 890 lbs



15 Year Manufacturer's Warranty
8 Year Manufacturer's High Traffic Warranty



Flo-Rite Drainage Technology

